

SKU	76524	76525	76526	76542	76543
Model	XM30	XM38	XM50	XP38	XP50
Microbolometer, resolution, pixels @ pixel pitch, μm	320x240 @ 12	320x240 @ 12	320x240 @ 12	640x480 @ 17	640x480 @ 17
Display, type / resolution, pixels	AMOLED 1024x768				
Objective lens	F30/1.25	F38/1.2	F50/1.2	F38/1.2	F50/1.2
Frame rate, Hz	50	50	50	50	50
Magnification, x	3.5 - 14	4 - 16	5.5 - 22	1.5 - 12	2 - 16
Range of detection, yds	1450	1850	2500	1500	2000
Windage & Elevation, 1 click , mm@100m	12	10	7	28	21
Operating Temperature, °F	- 13 ÷ +122	- 13 ÷ +122	- 13 ÷ +122	- 13 ÷ +122	- 13 ÷ +122
Weight, oz	26.45	26.45	31.7	26.45	31.7







Mounts on Standard 30mm Scope Rings

Designed from the ground up for ease of use. Thermion riflescopes mount to standard 30mm scope rings. No specialized tools or equipment are required.

Extreme Detection Range 2.500 Yds

High quality germanium optics coupled with an advanced thermal imaging sensor ensure an unprecedented detection range of up to 2,500 yards even in complete darkness.



Thermion riflescopes have dual battery system which consists of two batteries internal and external, External battery ensures additional operation time and can be replaced in a matter of seconds.



Recoil Rated up to .375 H&H, 12-Gauge and 9.3x64

Video and Still-Photo Recording

Integrated video (including recoilactivated) and still image recording in MPEG-4 and .jpg makes sharing the thermal action quick and easy. The onboard 16-GB internal memory handles recoil flawlessly and stores hours of video or thousands of photos.


Rugged, Reliable All-Metal Housing

Recoil rated up to 6,000 joules for flawless

12-gauge and 9.3x64.

performance on larger calibers up to .375 H&H,

Designed for rugged reliability, Thermion riflescopes boast full, reinforced vet lightweight metall construction. Precisionfabrication of housing elements ensures flawless field performance.



Color Palettes

Color palettes offer customized display options. While white hot and black hot are most popular, Red Hot. Rainbow and Ultramarine highlight a heat signature's more intense hot spots. Violet, Red Monochrome and Sepia are optimal palettes for reduced eye fatigue over long periods of observation.

Full-Color. **HD AMOLED Display**

While the Thermion's HD AMOLED display delivers crisp. richly contrasted, vividly colored field of view, AMOLED technology ensures flawless, fluid, highresolution imaging and power saving.

Instant Start-Up

Thanks to the new revolutionary electronics unit can be started almost instantly. Quick start-up helps to save energy and thus prolongs time of operation. The unit can be kept switched off and then rapidly activated when the right time comes.

User Friendly Controls

Thermion operation and adjustments are simple using the 3 function buttons on the top of the device and left side encoder. The 3 buttons and encoder provide access and management of all device menu options, settings and system functions.

High Definition Image

Sharp, richly contrasted thermal imaging for enhanced identification of animals. their extremities and even the smallest details, i.e. branches, leaves, grass and terrain.

Zeroing Profiles Management

Store up to 5 zeroing profiles, with 10 distance coordinates each for varying situations, in internal memory for quick rifle change-outs and on-the-fly adjustments

Zeroing Profiles Management

Store up to 5 zeroing profile with 10 distance coordinates each for varying situations, in internal memory for quick rifle change-outs and on-the-fly adjustments

Customizable Reticle Options

Wide array of color-customizable reticles, including scalable ballistic styles. Color options: black, white. red and green.

Picture-in-Picture

Picture-in-picture displays a magnified image at the top-center 10% of the overall field of view for precise shot placement. precise shot placement.

Variable Digital Zoom

Digital zoom, up to 8x, provides improved focus and overall target recognition at significant distances.

Picture-in-Picture

Picture-in-picture displays a magnified image at the top-center 10% of the overall field of view for

Stream Vision App Supported Using Wi-Fi and the Stream Vision App.

connect the Thermion to a smartphone or tablet for use as a second display or remote control. also makes transferring recorded files, adjusting settings, upgrading firmware.





STREAM

